


Multi-functional blinds for healthy environment!



Antibacterial



Deodorization



UV Protection



Mite Prevention



What is Green Guard?

US Certification on Eco-friendly product for Air Quality

- UL: Environmental assessment institute of U.S Standards System
- This Certification offers strict standards on the method, examination, sampling
- Rigorous standard on harmful effects on the human body
- GREENGUARD GOLD Certification is acceptable for use in schools and healthcare facilities
- Use GREENGUARD product and save the environment!

Acquired GREENGUARD Certification by UL U.S – international safety standard certification institution



UL U.S was founded in 2001 for protecting human health and quality of life from chemical material exposure & Indoor Air Quality. Our Bio collection products acquired GREENGUARD Certification.

What is Green Guard?

Environmental Evaluation Research Institute for UL Certification of the US

It is a global safety certification company that has been trusted across the world, and offers certification by applying strict criteria for all products that can affect indoor air quality.

Eco-friendly certification for indoor air quality

It is considerably difficult to obtain this certification due to strict criteria in test methods and criteria, sampling and the number of tests. Therefore, a product that has obtained this certification is an eco-friendly product so it is a criterion for purchase.

Strict criteria through consideration of harmfulness for humans

Gold certification covers safety for children and respiratory patients sensitive to environments, and certified products are proper for use even in schools and medical facilities.

Possible environment protection just by using Greenguard certified products

It is international certification that can be achieved only if all manufacturing processes are eco-friendly.





GREENGUARD Certification

GREENGUARD certification makes you feel more comfortable



Acquired GREENGUARD Certification by UL
U.S – international safety standard certification institution

It's the product recommended for people who don't use curtains
because of frequent allergic reactions, weak skin, and weak respiratory
system.

FDA Antibacterial fibers

Multi-functional Blinds for Healthy Environment! ATB-UV+



A future generation of antibacterial textile, ATB-UV+ is cutting-edge
textile which provide healthy environment by anti-bacterial functionality
of 99.9% by silver.



Antibacterial



Deodorization



UV Protection



Mite Prevention

Far infrared ray

Bio Product plus far-infrared health



Quality certification designated
company of Korea Far Infrared
Association

Deodorization and humidity control effects have been added through
functional materials emitting far infrared rays.

FAR INFRARED RADIATION RATE 89.3%

Thermal
action

Antibacterial
action

Blood
circulation

Humidity
control

Excellent
deodorizing
power



Far infrared ray



Antibacterial



Deodorization




UV Protection



Mite Prevention

FAR INFRARED RAY

Health is added to Bio Blinds!



Far infrared ray



Antibacterial



Deodorization



UV Protection



Mite Prevention

FAR INFRARED RAY

It is an infrared ray with a wavelength of $25\mu\text{m}$ or more. It is invisible to human eyes because it has longer wavelengths than visible light. It has a greater thermal action and strong penetration power. In addition, it shows a strong resonance and resonant action to organic compound molecules. Based on these properties, it has been widely applied to various industries and medical fields.

Far Infrared
FAR INFRARED




한국원자력의전협회



KFIA
KOREA FAR INFRARED
ASSOCIATION



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
ULCOM/GG
UL 2818



FAR INFRARED RAY

Health is added to Bio Blinds!

BIO
COLLECTION



Deodorization and humidity control effects have been added through functional materials emitting far infrared rays.

Far infrared radiation rate
89.3%

Far infrared rays of yellow soil radiation rate 93%

Thermal action

Antibacterial action

Blood circulation

Humidity control

Excellent deodorizing power

You can protect health of your family with Magic far infrared ray effects using far infrared functional yarns for bio products.

Efficacy of Far-infrared rays

- Have the most beneficial wavelengths for the human body and penetrate into our skin deeply, making our body warm and relaxed.
- Helpful for eliminating bacteria that are reasons of various diseases.
- Useful in expanding capillary blood vessels and helping blood circulation.
- Possible to promote metabolism, and prevent aging, chronic fatigue and adult diseases by activating cellular tissues.
- Useful in promoting perspiration, relieving pains, removing heavy metals, promoting deep sleep, deodorizing, preventing mold growth, dehumidifying, and purifying air.

■ TEST REPORT ■

01. Colorfastness to light: (KS K ISO 105 B02: 2014, Xenon-Arc-Lamp, Blue Scale): Grade

	#1
Blue Scale 5	Above 5
Blue Scale 6	Above 6

02. Efficiency of Deodorization(Fiti ftm-5-2: 2004) : %

	#1
Ammonia	29.0

Note) • Sample : 10cm×10cm • Initial Concentration : Ammonia(100ppm)
 • Gas Bag Size : 5L • Deodorization efficiency(%) = $(C_b - C_s/C_b) \times 100$
 • Amount of gas packed : 3L – C_b : Blank, Concentration of the test gas remained in the gas bag after 2 hours
 • Elapsed Time : After 2 Hours – C_s : sample, Concentration of the test gas remained in the gas bag after 2 hours


03. Antibacterial activity of textiles(k s k 0693: 2016): cells/mL, Bacteriostatic reduction rate %

		BLANK	#1
Bacteria 1	At beginning	1.8×10^4	–
	after 18 h	8.7×10^6	1.8×10^4
	Bacteriostatic Reduction Rate	–	99.8
Bacteria 2	At beginning	1.8×10^4	–
	after 18 h	2.7×10^7	2.5×10^5
	Bacteriostatic Reduction Rate	–	99.1

Note) Standard Fabric : Cotton

Nonionic surfactant agents : TWEEN 80, 0.05%

Test bacteria: Bacteria 1-Staphylococcus aureus ATCC 6538, / Bacteria 2-Klebsiella pneumoniae ATCC 4352.




Korea Far Infrared association test report

MARS

FAR INFRARED RAY




IM 5814 LIGHT BEIGE




IM 5811 WHITE




IM 5815 GREY




IM 5816 OLIVE GOLD



IM 5819 CHARCOAL



IM 5820 NAVY



IM 5820 NAVY



MARS

FAR INFRARED RAY

Technical Data




• Composition	Polyester 100%
• Thickness	0.49mm ±5%
• Weight	188.7g / m ² ±5%
• Width	280cm
• Tensile strength	Warp 2600dan
• Packing	40m/roll
• Fastness to light	Above 6 grade




RAY


FAR INFRARED RAY






IR 5902 IVORY




IR 5903 MUSHROOM



IR 5904 LIGHT GREY



IR 5908 LIGHT GREEN



IR 5909 BLUE




RAY

FAR INFRARED RAY

Technical Data



- Composition Polyester 100%
- Thickness $0.38\text{mm}\pm 5\%$
- Weight $129.1\text{g/m}^2\pm 5\%$
- Width 280cm
- Tensile strength Warp 1600dan
- Packing 50m/roll
- Fastness to light Above 6 grade




Far Infrared ray Antibacterial Deodorization UV Protection Mite Prevention

친환경인증획득

원적외선인증획득

GRACE


FAR INFRARED RAY




IG 5931 INK BLUE




IG 5923 BEIGE



IG 5925 GREY



IG 5926 LIGHT BROWN



IG 5929 WINE




GRACE FAR INFRARED RAY

Technical Data



- Composition Polyester 100%
- Thickness $0.40\text{mm} \pm 5\%$
- Weight $122.8, 2\text{g / m}^2 \pm 5\%$
- Width 280cm
- Tensile strength Warp 1600dan
- Packing 50m/roll
- Fastness to light Above 4 grade



친환경인증획득




원적외선인증획득

- 원적외선 Far infrared ray
- 항균 Antibacterial
- 탈취 Deodorization
- UV차단 UV Protection
- 진드기 방지 Mite Prevention




BIO ALICE


BLACK OUT



BA 4401



BA 4402



BA 4403



BA 4404

BIO ALICE

Technical Data




- Composition Polyester 100%
- Thickness $0.50\text{mm} \pm 5\%$
- Weight $207.230\text{g/m}^2 \pm 5\%$
- Width 280cm
- Tensile strength warp 2400dan / weft 1400dan
- Packing 40m/roll
- Elongation warp 24.6% / weft 12%
- Fastness to light Above 4 grade

BLACK OUT



Antibacterial Deodorization UV Protection Mite Prevention




BIO ELDORA

BLACK OUT




BE 4207 DARK GREY




BE 4208 CHOCOLATE CHIP



BE 4210 BROWN



BE 4205 KHAKI



BE 4206 LIGHT GREY





BIO ELDORA


Technical Data




- Composition Polyester 100%
- Thickness $0.58\text{mm} \pm 5\%$
- Weight $349.8\text{g/m}^2 \pm 5\%$
- Width 280cm
- Tensile strength weft 2600dan
- Packing 40m/roll
- Elongation weft 24.1%
- Fastness to light Above 4 grade



BLACK OUT




BIO VIVIAN



BV 4902 MUSHROOM



BV 4903 GREY



BV 4905 KHAKI



BV 4906 OLIVE GOLD



BV 4907 INK BLACK



BIO VIVIAN

Technical Data

- Composition: Polyester 100%
- Thickness: 0,40mm±5%
- Weight: 159,61g/m²±5%
- Width: 280cm
- Tensile strength: warp 209,5dan / weft 25,2dan
- Packing: 50m/roll
- Elongation: warp 23,1% / weft 11,1%
- Fastness to light: Above 4 grade



GREENGUARD
PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818

Antibacterial Deodorization UV Protection Mite Prevention


BIO CLEAN SHADE



BS 4301 WHITE



BS 4305 LIGHT GREY



BS 4308 KHAKI



BS 4309 INK BLACK



BIO CLEAN SHADE

Technical Data




• Composition	Polyester 100%
• Thickness	0.34mm±5%
• Weight	116.0g/m ² ±5%
• Width	280cm
• Tensile strength	warp 1400dan / weft 2400dan
• Packing	50m/roll
• Elongation	warp 11.7% / weft 12%
• Fastness to light	Above 4 grade



Antibacterial Deodorization UV Protection Mite Prevention



BIO VENUS




BN 4805 INK BLACK




BN 4803 GREY



BN 4806 BLUE



BN 4807 WINE



BN 4808 BROWN

BIO VENUS

Technical Data

• Composition	Polyester 100%
• Thickness	0.39mm±5%
• Weight	116.0g / m ² ±5%
• Width	280cm
• Tensile strength	warp 1400dan
• Packing	50m/roll
• Fastness to light	Above 6 grade



Antibacterial Deodorization UV Protection Mite Prevention


GOLD




BIO SOPHIA




BS 4606 GREY



BS 4601 IVORY



BS 4610 BEIGE



BS 4613 LIGHT GREEN



BS 4617 PURPLE




BS 4607 KHAKI



BS 4602 MUSHROOM



BS 4604 BLUE



BS 4605 WINE



BS 4615 DARK BEIGE



BS 4618 WOOD



BIO SOPHIA

Technical Data

- Composition Polyester 100%
- Thickness $0.42\text{mm} \pm 5\%$
- Weight $149.50\text{g / m}^2 \pm 5\%$
- Width 280cm
- Tensile strength warp 2400dan / weft 1400dan
- Packing 50m/roll
- Elongation warp 24.6% / weft 12%
- Fastness to light Above 4 grade





Antibacterial Deodorization UV Protection Mite Prevention




LAMIS MAGIC

FR

BLACK OUT




LM 8102 LIGHT GREY




LM 8101 MUSHROOM




LM 8104 DARK GREY



LM 8106 INK BLACK




LM 8103 MEDIUM GREY



LM 8105 WOOD





LAMIS MAGIC

Technical Data




- Composition Polyester 100%
- Thickness $0.47\text{mm} \pm 5\%$
- Weight $140\text{g / m}^2 \pm 5\%$
- Width 280cm
- Tensile strength Welt 2300dan
- Packing 50m/roll
- Elongation Welt 32,5%
- Fastness to light Above 4 grade




SIERRA MAGIC


BLACK OUT




SM 7907 WOOD




SM 7901 WHITE



SM 7902 IVORY



SM 7905 DARK GREY



SM 7908 INK BLACK



SM 7906 CHARCOAL

SIERRA MAGIC

Technical Data




- Composition Polyester 100%
- Thickness 0,46mm ±5%
- Weight 173g / m² ±5%
- Width 280cm
- Tensile strength Weft 2200dan
- Packing 50m/roll
- Elongation Weft 30,3%
- Fastness to light Above 4 grade

BLACK OUT




SEAGULL



SG 7806 CHARCOAL




SG 7801 MUSHROOM




SG 7802 LIGHT GREY



SG 7803 LIGHT BLUE



SG 7804 DARK GREEN



SG 7805 GREY



SG 7807 WOOD

SEAGULL




Technical Data




- Composition Polyester 100%
- Thickness $0.38\text{mm} \pm 5\%$
- Weight $168.9\text{g/m}^2 \pm 5\%$
- Width 320cm
- Tensile strength Welt 2100dan
- Packing 40m/roll
- Fastness to light Above 6 grade




TOSCA




TO 7004 BROWN




TO 7001 LIGHT GREY



TO 7003 DARK GREY



TO 7006 BLACK



TO 7002 GREY



TO 7005 NAVY




TOSCA

Technical Data


- Composition Polyester 100%
- Thickness 0,40mm ±5%
- Weight 153,4g/m² ±5%
- Width 320cm
- Tensile strength weft 1800 N
- Packing 40m/roll
- Fastness to light Above 6 grade




AIDA



AI 8607 BROWN




AI 8602 LIGHT GREY



AI 8604 MUSHROOM



AI 8609 CHOCO



AI 8611 MEDIUM GREY



AI 8614 CHARCOAL



AI 8615 DARK BLUE



AIDA


Technical Data



- Composition Polyester 100%
- Thickness 0,53mm ± 5%
- Weight 205,3g / m² ± 5%
- Width 320cm
- Tensile strength Weft 2600 N
- Packing 40m/roll
- Fastness to light Above 6 grade



TONO



TONO
TN 6301 WHITE



TN 6302 MUSHROOM



TN 6303 NAVY



TN 6304 BLACK




TONO


Technical Data



- Composition Polyester 100%
- Thickness 0,40mm ±5%
- Weight 148,3g/m² ±5%
- Width 280cm
- Tensile strength Weft 2600 N
- Packing 50m/roll
- Fastness to light Above 6 grade




RAINBOW MAGIC



RM 4001 WHITE



RM 4002 IVORY



RM 4005 GREY



RM 4008 INK BLACK



RM 4006 WOOD

RAINBOW MAGIC

Technical Data




- Composition Polyester 100%
- Thickness $0.31\text{mm} \pm 5\%$
- Weight $109.5\text{g / m}^2 \pm 5\%$
- Width 280cm
- Tensile strength Warp 98,1dan / Weft 1314,7dan
- Packing 50m/roll
- Elongation Warp 11,3% / Weft 22,6%
- Fastness to light Above 4 grade




PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818

GOLD



CELLO MAGIC




CM 702 MUSHROOM



CM 701 IVORY



CM 703 BEIGE



CM 707 GREY



CM 708 BROWN



CM 710 WOOD



CM 711 INK BLACK



CELLO MAGIC

Technical Data



• Composition	Polyester 100%
• Thickness	0,60mm±5%
• Weight	140g /m ² ±5%
• Width	280cm
• Tensile strength	Warp 253,0dan / Welt 225,2dan
• Packing	50m/roll
• Elongation	Warp 23% / Welt 11,2%
• Fastness to light	Above 4 grade



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL-COM/GG
UL 2818

GOLD

